

Approval Drawings

Opéra Series Electric Radiant Heater









7736 Opéra 17 -Standard Profile



7737 Opéra 46 -Tall Profile

FEATURES

Color - Satin white

Finish - Epoxy/polyester anti-rust powder coating resistant to UV rays

Voltage - 240/208 V, 60 Hz, 1-phase

Wattage - 7735 - Sizes ranging from 750 W and 1,000 W

- 7736 - Sizes ranging from 500 W, 1,000 W, 1,500 W and 2000 W

7737 - Sizes ranging from 1,000 W, 1,500 W and 2000 W

Construction - Convex casing with rounded corners

- Perforated front panel for better radiant heat diffusion with absence detector

High-limit temperature control with automatic reset

Heating Element -

High-efficiency monoblock element constructed from ribbed aluminum alloy

Control

Programmable built-in electronic proportional-action digital thermostat, ultra-precise to 1/10 °C (1/5 °F), located at the top of the unit

- LCD backlit display with digital controls lockable by key combination and the ability to add a code for unlocking

Temperature display format (°C or °F)

- "On-Off" button

- "Manual" button to choose from Comfort, Economy and Frost Protection modes

- "Open-window" button to activate the open-window detection function

- "Automatic" button

Energy use indicator

Heating indicator light

- Absence detector (setback when absence is detected, and this function is activated

Installation

Quick surface-mounted installation, with the included wall-mounting bracket, that

also serves as marking template

- Flexible cable with electrical wall box cover plate included

Requires installation of a wall electrical box not supplied


Warranty - 5-year heating element, 2-year parts and defects


Applications - Kitchen, living room, family room, bedroom, bay window




Approval Drawings

Opéra Series Electric Radiant Heater







Note: The depth shown includes wall bracket.

Product No.	QTY	UPC	VOLTS	WATTS	HEIGHT		WIDTH		DEPTH		WEIGHT		
Product No.					IN	СМ	IN	СМ	IN	СМ	LB	KG	
7735 Opéra 12 - Low Profile - SATIN WHITE													
X-7735-C07-FS		774725006400	240/208	750/565	11-3/16	28.4	35-3/16	85.0	4-1/8	10.5	12.1	5.5	
X-7735-C10-FS		774725006417	240/208	1000/750	11-3/16	28.4	41-3/4	106.0	4-1/8	10.5	13.4	6.1	
7736 Opéra 17 - Standard Profile - SATIN WHITE													
X-7736-C05-FS		774725006424	240/208	500/375	17-5/16	44.0	20-15/16	53.2	4-1/2	11.3	9.7	4.4	
X-7736-C10-FS		774725006431	240/208	1,000/750	17-5/16	44.0	25-1/16	63.7	4-1/2	11.3	11.7	5.3	
X-7736-C15-FS		774725006448	240/208	1,500/1,125	17-5/16	44.0	33-3/8	84.5	4-1/2	11.3	15.4	7.0	
X-7736-C20-FS		774725006455	240/208	2,000/1,500	17-5/16	44.0	41-5/8	105.4	4-1/2	11.3	19.2	8.6	
7737 Opéra 46 - Tall profile - SATIN WHITE													
X-7737-C10-FS		774725006462	240/208	1,000/750	33-3/8	84.7	17-5/16	44.0	4-13/16	12.3	15.4	7.0	
X-7737-C15-FS		774725006479	240/208	1,500/1,125	41-5/16	105.7	17-5/16	44.0	4-13/16	12.3	17.6	8.7	
X-7737-C20-FS		774725006486	240/208	2,000/1,500	45-11/16	116.2	17-5/16	44.0	4-13/16	12.3	19.8	9.5	

Project Details

Project:	
Consulting Engineer:	
Electrical Contractor:	
Distributor:	
Date:	
Contact at Glen Dimplex Americas:	Approval Information
Comments:	

1-800-668-6663 | convectair.ca